

RT2360 Dispersant

Overview:

RT2360 is a wetting and dispersing agent for water-based printing inks and coatings. It reduces abrasive viscosity, improves storage stability of coatings, enhances compatibility between various pigments and emulsion, and effectively improves color vibrancy and gloss.

Reference technical specifications:

Appearance	Yellowish to brownish-yellow liquid
Chemical composition	Aqueous solution of polymer surfactant containing group, which has high affinity pigment
Active content	About 35%
pH	7-10

Advantages:

- Used in carbon black and organic pigments
- Significantly reduce the viscosity during grinding
- Primarily recommended for resin-containing grinding
- Excellent coloring power
- Solvent-free and ethoxynonylphenol-free

Applications:

Waterborne Industrial Coatings

Waterborne Inks

Recommended dosage:

Class	Titanium pigment	Organic pigment	Inorganic pigment
Amount% (relative to pigment)	1.0~5.0	10.0~30.0	4.0~10.0

Package and storage:

Store in a dark place, keep unopened and stored at 5°C to 35°C. The product has a shelf life of 12 months from the date of production.

Available in 30kg/bucket and 200kg/bucket sizes, with customized packaging options for customers.



All data, including formulations, are authentic. However, customers must conduct experiments in their own laboratories or equipment for confirmation, and the company cannot make any commitments. Customers must comply with local patent regulations. Suppliers have the right to improve their products, and any modifications to specifications may be made without prior notice.