

RT820A Anti-foaming Agent

Overview:

RT820A is a high-performance anti-foaming agent specifically engineered to address severe foaming issues in medium-to-low PVC latex paints. It is recommended for use in interior/exterior wall paints and colored primers, offering broad application and excellent cost-effectiveness.

Product advantages:

- Exhibits exceptional anti-foaming performance in conventional architectural coatings;
- Suitable for interior/exterior wall paints and primers.

Reference technical specification:

Chemical Composition: Mineral oil-based defoamer

Active content: Approximately 100%

Appearance: Colorless to yellowish opaque liquid

Specific gravity (25°C): 0.80-1.0 (25°C)

Typical application:

Water-based 2K waterproofing coating

Recommended amount:

- 0.1-0.5% of the total formulation.

Description of the process:

- We recommend equal parts for pulp preparation and paint mixing stages, with specific quantities to be adjusted by the client based on actual conditions.
- Freezing should be avoided, and the product must be thoroughly stirred or shaken before use.

Package and Storage:

Store in a dark place, keep unopened and stored at 5°C to 35°C. The product has a shelf life of 12 months from the date of production.

Available in 25kg/bucket and 180kg/bucket sizes, with customized packaging options for customers.



All data, including formulations, are authentic. However, customers must conduct experiments in their own laboratories or equipment for confirmation, and the company cannot make any commitments. Customers must comply with local patent regulations. Suppliers have the right to improve their products, and any modifications to specifications may be made without prior notice.