

RT8560T defoaming agent

Overview:

RT8560T is a defoamer specifically formulated for thick-paste coatings, delivering exceptional long-lasting foam suppression. It excels in suppressing and breaking foam in water-based coating systems, making it particularly suitable for high-viscosity latex paints used in roller application processes.

Product advantages:

- It has strong defoaming effect in ordinary building coatings.
- for high viscosity coatings;
- The defoaming property is good.

Reference technical indicators:

Chemical Composition: Silicone-based mineral oil defoamer

Active content: approximately 100%

Appearance: Colorless to yellowish opaque liquid

Specific gravity (25°C): 0.8-1 g/ml

Typical application:

Building coating thick paint

Recommended amount:

- 0.1-1.0% of the total formulation.

Description of the process

- The specific dosage should be adjusted by the customer according to actual conditions.
- Freezing should be avoided, and the product must be thoroughly stirred or shaken before use.

Package and Storage:

Store in a dark place, keep unopened and stored at 5°C to 35°C. The product has a shelf life of 12 months from the date of production.

Available in 25kg/bucket and 180kg/bucket sizes, with customized packaging options for customers.

CELOTECH **RUICO**

All data, including formulations, are authentic. However, customers must conduct experiments in their own laboratories or equipment for confirmation, and the company cannot make any commitments. Customers must comply with local patent regulations. Suppliers have the right to improve their products, and any modifications to specifications may be made without prior notice.