

RT8086 Defoaming Agent

Overview :

RT8086 is a specialized defoamer for two-component waterproof coating that also delivers outstanding performance in 2K waterproof systems. With excellent water dispersibility and compatibility, it offers a broader range of applications and superior performance.

Product advantages:

- The addition amount is small, and there is no oil spot defect;
- It performs exceptionally well in 2K waterproof coatings.
- The defoaming efficiency and compatibility have reached a good balance.

Reference technical specifications:

Chemical Composition: Polyether Mineral Oil-based Defoaming Agent

Active content: approximately 100%

Appearance: Colorless to pale yellow opaque liquid

Specific gravity (25°C): 0.8-1 g/ml (25°C)

Typical application:

Waterborne 2K Waterproofing, Waterborne Adhesive, Waterborne Ink Printing, Architectural Coatings

Recommended amount:

0.05-0.5% of the total formulation.

Description of the process:

- The specific dosage should be adjusted by the customer according to actual conditions.
- Freezing should be avoided, and the product must be thoroughly stirred or shaken before use.

CELOTECH **RUICO**

Package and Storage:

Store in a dark place, keep unopened and stored at 5°C to 35°C. The product has a shelf life of 12 months from the date of production.

Available in 25kg/bucket and 180kg/bucket sizes, with customized packaging options for customers.

All data, including formulations, are authentic. However, customers must conduct experiments in their own laboratories or equipment for confirmation, and the company cannot make any commitments. Customers must comply with local patent regulations. Suppliers have the right to improve their products, and any modifications to specifications may be made without prior notice.